ThinkVision P32p-20 62A2GAT2EU

Product

ThinkVision P32p-20

Machine Type 62A2

Region EMEA

Display Size 31.5"

View Area 697.31x392.23 mm

Panel In-Plane Switching

Aspect Ratio 16:9

Resolution 3840x2160

Pixel Pitch 0.1816x0.1816 mm

Dot / Pixel Per Inch 140 dpi

View Angle (H / V) 178 / 178

Response Time 4 ms (Extreme mode) / 6 ms (Typical mode) / 14 ms (Off mode)

Color Support 1.07 Billion

Refresh Rate 60 Hz

Brightness 350 nits

Contrast Ratio 1000:1

Color Gamut 99% sRGB, 99% BT.709, 90% DCI-P3

Curvature None

Anti-glare Yes

Video Connector 1x HDMI 2.0, 1x DP 1.2, 1x USB Type-C 3.2 Gen 1 (DP 1.2 Alt Mode)

USB Port 3x USB 3.2 Gen 1 (1x BC 1.2)

Camera ThinkVision MC 50 Support

Microphone None

Speakers None Power Consumption (Typical / Maximum) 36W / 186W

Power Adapter Integrated

Stand Tilt, Swivel, Height Adjust Stand

Color Raven Black

Side Bezel Width 2 mm

Dimensions with Stand (HxWxD) 604.4x714.6x235 mm / 23.8x28.13x9.25 inches

Weight (Including Stand) 10.21 kg / 22.51 lbs.

Cables Included USB Type-C to Type-C cable, USB Type-A to Type-B cable

Environmental Certification Energy Star Certified, TCO 8.0, TCO Edge 2.0, EPEAT Gold, RoHS

Ergonomic Certification TÜV Rheinland Eye Comfort

Base Warranty 3-year

Operating System Support Support Windows 7, Windows 10

Sync Technology None

Tiny Support / CPU / Platform Tiny Support, Nano Support / None / None

Ethernet / Bluetooth / Wireless Ethernet (10M/100M/1000M) / None / None

Touch Screen / Digitizer Pen / Battery None / None / None

Display Ram / Storage / Card Slot None / None / None

EAN / UPC / JAN 0194778267830 / 194778267830 / None

Announce Date 2020-06-30

L WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.

https://psref.lenovo.com

PSREF

Visit psref website for the latest version of Product specifications Reference. © Lenovo, 2022. All rights reserved.



ThinkVision P32p-20

DISPLAY

Panel Size 31.5-inch

Screen Dimensions 697.31 mm x 392.23 mm

Panel Type 3-side NearEdgeless In-Plane Switching

Backlight WLED

Aspect Ratio 16:9

Resolution 3840 x 2160

Pixel Pitch 0.1816 x 0.1816 mm

Dot/Pixel Per Inch (DPI/PPI) 140

Viewing Angle (H x V @ CR 10:1) 178° / 178°

Response Time 4ms (extreme mode) 6ms (normal mode)

Refresh Rate 60 Hz

Brightness (typical) 350 cd/m²

Contrast Ratio (typical)

Dynamic Contrast Ratio (typical) 3M:1

Color Gamut 99% sRGB 99% BT.709 90% DCI-P3 Color Support (typical) 1.07 Billion

Color Depth 10-bit

Processor LUT 14-bit

Anti-glare Yes

CONNECTIVITY

Video Signal 1 x USB Type-C¹ Gen1 (DP1.2 Alt Mode) 1 x HDMI 2.0 1 x DP 1.2

Audio Signal 1 x Audio Out (3.5 mm)

USB Hub Yes

Ethernet Yes (10M/100M/1000M)

USB Upstream 2 x USB 3.2 Gen1 (1 by USB Type-C, 1 by USB Type-B)

USB Downstream 3 x USB 3.2 Gen1 (1 x BC1.2)

MULTI-MEDIA

Optional Soundbar Support Yes (PN:0A36190)

SPECIAL FEATURES

Factory Calibration Yes (Avg. Delta E<2)

Software Lenovo ThinkColour (Lenovo Display Control Center)²

POWER

Power Consumption (typ./max.) 36W / 186W

Power Consumption Sleep/O Mode < 0.5W

Power Consumption Switch-o Mode < 0.3W

ENERGY STAR Power Consumption (P_{on}/E_{TEC}) 27W / 84kWh

Power Supply Internal

USB Type-C Power Delivery (W) up to 90 W³

Voltage Required AC 100 to 240 V (50-60 Hz)

MECHANICAL

Tilt Angle (front/back) -5° / 35°

Swivel Angle (left/right) +45° / -45°

Lift (max. range) 135 mm

Pivot -90° / 90°

> VESA Mount Capability Yes (100 x 100 mm)

ThinkCentre M Series Tiny support Yes, by Tiny/Nano monitor clamp II (PN: 4XHOZ42451) & Tiny VESA mount II (PN: 4XFONO3161)⁴ ThinkCentre M Series Nano support Yes, by Tiny/Nano monitor clamp II (PN: 4XHOZ42451) & Nano VESA mount (PN: 4XFOV81630)⁴

Kensington Lock Slot Yes

Cable Management Yes

Bezel Color Raven Black

Bezel Width (side) 2.0 mm

Bezel Width (top/bottom) 2.0 / 24.1 mm

DIMENSION

Size Packed (D x H x W, mm/inch) 528 x 190 x 845 mm 20.79 x 7.48 x 32.27 inches

Size Unpacked w/ Stand (D x H x W, mm/inch) (lowest position) 235.0 x 469.4 x 714.6 mm 9.25 x 18.48 x 28.13 inches

Size Unpacked w/ Stand (D x H x W, mm/inch) (highest position) 235.0 x 604.4 x 714.6 mm 9.25 x 23.79 x 28.13 inches

Size Unpacked w/o Stand (head only) (D x H x W, mm/inch) 714.6 x 426.0 x 51.0 mm 28.13 x 16.77 x 2.01 inches

Weight Packed (kg/lbs.) 13.30 kg/29.32 lbs.

Weight Unpacked (kg/lbs.) 10.21 kg/22.51 lbs.

Weight (monitor head only) (kg/lbs.) 6.96 kg/15.34 lbs.

WHAT'S IN THE BOX

Monitor with stand 1 x Power cable (1.8 m) 1 x DP cable (1.8 m) (for US and Canada only) 1 x USB Type-C to Type-C cable (1.8 m) 1 x USB Type-A to Type-B cable (1.8 m) Factory calibration report Quick setup guide

CERTIFICATION

ENERGY STAR Yes

CCC Yes

тсо

8.0

TCO Edge 2.0

-

EPEAT Gold

RoHS (EU 2002/95/EC) Yes

Windows Certification Windows 7, Windows 10

China Energy E ciency Standard Tier 1

TÜV Rheinland Eye Comfort Yes



Windows

¹USB Type-C[®] and USB-C[®] are registered trademarks of USB Implementers Forum. ²This software can only be used with Windows 10

¹ Up to 90W power delivery to compatible devices by USB Type-C. Listed as maximum capacity of power delivery. Actual capacity may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting. ⁴Accessories sold separately

KVM Switch

Yes

Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen1; 10 Gbit/s for USB 3.1 Gen2 & 20 Gbit/s for USB 3.2.

© 2021 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkVantage, and ThinkVision are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks of others. Specifications may vary depending upon region. ThinkVision P32p-20







